所別:機械工程學系碩士班 甲組(固力與設計)(一般生) 科目:動力學 共 機械工程學系碩士班 丁組(系統)(一般生)

光機電工程研究所碩士班 甲組(機電系統控制)(一般生)


\*本科考証

\*本科考試可使用計算器,廠牌、功能不拘


\*請在試卷答案卷(卡)內作答

1. (25%) The quarter-circular hollow tube of circular cross section rotates in a horizontal plane with a constant angular acceleration  $\ddot{\theta} = 1 \text{ rad/s}^2$ . It starts from rest at time t = 0 from the position  $\theta = 0$ . At what time t will the 1-kg particle P slips relative to the tube? The coefficient of static friction between particle P and the tube is  $\mu_s = 0.8$  and that of kinetic friction is  $\mu_k = 0.6$ . (Points will be given only if free body diagram is used.)


光機電工程研究所碩士班 乙組(光機)(一般生)



- 2. (25%) The 100-kg spool shown has a radius of gyration  $k_G = 0.35$  m. A cable is wrapped around the central hub of the spool and a variable horizontal force having a magnitude of P = (t+10) N is applied, where t is measured in seconds. Assume that the spool rolls without slipping at A.
  - (A) (10%) Draw the free-body diagram and the kinetic diagram, respectively. (Kinetic Diagram: a diagram to illustrate all resulting motion on a free body.)
  - (b) (15%) If the spool is initially at rest, determine its angular velocity in 5 s.



3. (25%) An energy-absorbing bumper has an equivalent spring constant 525 kN/m at its undeformed state. If the 1200-kg car approaches a rigid wall with a speed of 8 km/h, please determine (a) the velocity  $\nu$  of the car as a function of time during contact with the wall, where t=0 is the beginning of the impact, and (b) the maximum deflection  $x_{\text{max}}$  of the bumper. (Points will be given only if free body diagram is used.)



4. (25%) The stream of water shown flows at the rate of 0.9 m<sup>3</sup>/min and moves with a velocity of magnitude 30 m/s at both A and B. The vane is supported by a pin connection at C and by a load cell at D which can exert only a horizontal force. Neglecting the weight of the vane, determine the reactions at C and D.

